

DECHLOR DEMON™

DECHLORINATE WHILE HYDRANT
FLOW TESTING OR FLUSHING!

HOW DOES DECHLOR DEMON™ WORK?

1. A portion of the water flowing through the Dechlor Demon™ is diverted through the bypass into a mixing tank, where it is combined with a concentrated dechlorinating agent.
2. The bypass flow is controlled by a precision indicating valve.
3. The concentrate is reintroduced into the Dechlor Demon™ and hose, where it continues to mix with the flowing water.
4. The chlorine is neutralized by the time it exits the hose.

ACCESSORIES & OTHER PRODUCTS

HYDRANT FLOW TESTING BUNDLE

Everything you need to test and flow fire hydrants in one case.

VITA-D-CHLOR TABLETS

The safest and most environmentally conscious method of dechlorination.

BIO MAX DECHLORINATING TABLETS

The strongest products available for dechlorination.

BIO NEUTRALIZER DECHLORINATION TABLETS

Sodium sulfite tablets instantaneously reduce free and combined chlorine in water or wastewater to non-detectable levels without affecting dissolved oxygen.

NORWECO'S ENVIRO-C TABLETS

Enviro-C dechlorination tablets utilize the unique chemistry of vitamin C to neutralize chlorine and chloramines from water, wastewater and process water applications.

HOSE MONSTER
COMPANY

1330 Ensell Rd, Lake Zurich, IL 60047

 (888) 202-9987

 (847) 434-0073

 service@hosemonster.com

 hosemonster.com



SPECIFICATIONS

The Hose Monster Company's Dechlor Demon™ uses ascorbic acid or other dechlorination agents to neutralize chlorinated water during testing or flushing. The Dechlor Demon™ can work within your existing testing/flowing regimen without the need for an entire new setup. With its minimal moving parts and ease of use, the Dechlor Demon™ is one of the most effective dechlorinators available. Three sizes are available: 2½", 4" and 4½"

- Neutralizes high concentration of chlorine.
- Works at high- and low-volume flow rates.
- Low friction loss.
- Use with the Hose Monster® or almost any other device.
- Conserves dechlorination agent.
- Short length means no added stress to hydrant nozzles.
- Effective for flow testing, flushing and treating chlorinated water.

ITEMS #	
DD BODY 2½"	<ul style="list-style-type: none"> • Steel ASTM-A513/5 body • 2½" NH female swivel x 2½" NH male • 7" overall length including swivel coupling • 17" overall width including ball-valves and couplings • Weight is 8 pounds
DD BODY 4" AND 4½"	<ul style="list-style-type: none"> • Steel ASTM-A513/5 body • 4" NH female swivel x 4" NH male • 4½" NH female swivel x 4½" NH male • 7" overall length including swivel coupling • 17" overall width including ball-valves and couplings • Weight is 18 pounds
PICKUP TUBES	303 Stainless Steel
SWIVEL COUPLINGS	6016 T6 Hard Coated Aluminum
TUBES	⅝" ID PVC Nylon Braid Reinforced
QUICK DISCONNECT COUPLINGS	<ul style="list-style-type: none"> • Brass with 303 Stainless Steel Hardware • O-Rings–BUNA–N
MIXING TANK	<ul style="list-style-type: none"> • Polyethylene inner shell • Standard Tank Size 6"D x 18"H including manifold and couplings Capacity: 1.33 Gallons / 5.0 Liters • Large Capacity Tank Option Capacity: 10.2 Gallons / 38.6 Liters